



Product Description:

The SW 700 Screen Wash and Stain Remover is an environmentally approved, 100% active, low odor, extremely quick penetrating and fast acting solvent designed to dissolve and clean all types of screen printable inks, adhesives, clear coatings and stains from printing mesh. It also works quickly as a stain remover.

Special Features:

- SW 700 dissolves all inks and ink stains quickly, allowing mesh to be rinsed clean with water.
- SW 700 is a low odor product, providing a more pleasant environment for employees.
- This product contains no hazardous substances (no TLV's, no PEL's) which provides a better work-place environment.
- This product is non-flammable (flash point of 196° F) which makes it safer for handling, storage and rag disposal than conventional screen washes.
- This product contains low-foam, biodegradable detergents which contribute to superior ink and stain removal, while providing complete risibility with water.
- The SW 700 is not SARA (Superfund Amendments Reauthorization Act) reportable which requires less solvent monitoring and paper work.
- SW 700 may be applied manually or recirculated in enclosed, automatic screen washing systems, providing superior product life and economy.
- The 700 may be applied to a wet screen for use as a stain remover, without causing damage to the mesh.

Physical & Chemical Data:

Appearance & Odor	Clear amber liquid/mild odor
Specific Gravity	1.01 @ 20°C / 68°F
Vapor Pressure	0.08 mm Hg @ 20° C / 68°F
Vapor Density	Heavier than air
Boiling Point	196°C / 385°F
pH	Neutral
VOC	448 grams / liter
Flash Point	196 °F / 91 °C

Application:

Scrape all excess ink from screen. Apply SW 700 to the (well) ink and print side of the screen. Scrub if necessary. Squeegee excess off screen. Using a good high pressure washer, spray rinse the screen starting at the bottom of the well side and work up. Give good attention to the image area of the screen. Rinse the print side of the screen. Apply an approved emulsion/stencil remover. The screen will now be ready for reuse. If stubborn stains remain, apply SW 700 as a stain remover and high pressure rinse.

Note

This Technical Bulletin is intended to be used for informational purposes only, and is in no way intended to create any warranties or other obligations on behalf of Norcote. All warranties, terms and / or conditions for a particular product will be specified on the applicable invoice and are only valid upon the creation of a legally binding contract.

Testing

Due to the inability of Norcote to anticipate or control the conditions under which the products and information relating thereto will be used and / or stored, Norcote cannot guarantee the results obtained from using the products. Any suggested uses are merely representative, and because the final product will depend on a number of specific factors, the end user should pretest all substrates with products prior to use in production.

Revision: 11/06/2014
Supersedes: 05/02/2014